

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008078 A2

(51) International Patent Classification⁷: **F16B**

(21) International Application Number:
PCT/US2004/021827

(22) International Filing Date: 9 July 2004 (09.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/485,749 10 July 2003 (10.07.2003) US

(71) Applicant and

(72) Inventor: WICKLUND, James, Vanerd, Jr. [US/US];
94-363 Puaahi Place, Mililani, Hawaii 96789 (US).

(74) Agent: SLATTERY, James, M.; Birch, Stewart, Kolasch
& Birch, LLP, P.O. Box 747, Falls Church, VA 22040-0747
(US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished
upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: CLAMPING PLIERS



(57) Abstract: A clamping tool for use with a power tool includes a housing mounted on a power tool. The housing includes at least one engaging portion. The locking pliers includes a retaining section with a proximal end and a distal end. The proximal end is mounted on the at least one engaging portion for retain the locking pliers in a selectively, releasably, rotational relationship relative to the housing. An engaging section of the locking pliers is mounted relative to the retaining section and is selectively locked relative to the distal end of the retaining section for positioning an article therebetween. In two embodiments, after an article is locked in the locking pliers, the locking pliers can be rotated either away from or towards the housing to permit the power tool to come into engagement with an article.



WO 2005/008078 A2